

DM-441B

BENCH DIGITAL MULTIMETER





The DM-441B is a 4 1/2 digit, 20,000 count bench top multimeter. This True RMS meter has a basic accuracy of 0.1%. The DM-441B supports a full range of functions including: frequency, resistance, voltage, current with transistor check and added features like data hold, and continuity. The DM-441B is overload protected to 600 volts in the resistance ranges.



FEATURES

- 4 1/2 Digit display, 5 Digit Green LED, 19999 count
- Vdc Basic accuracy of 0.1%
- Full overload protection
- Frequency measurement up to 200kHz
- Continuity check with beeper
- Data hold, Diode check, TR hfe measurement available
- True RMS in AC range
- 600V overload protection in Resistance range





Specifications

BENCH DIGITAL MULTIMETER

31

FUNCTION	Range	Resolution	Accuracy
DC VOLTAGE	200mV	10 μ V	$\pm(0.1\%+4\text{digits})$
	2V	100 μ V	
	20V	1mV	
	200V	10mV	
	1000V	100mV	
AC VOLTAGE	200mV	10 μ A	$\pm(0.5\%+20\text{digits}), (45\text{Hz}\sim1\text{kHz})$ $\pm(0.8\%+10\text{digits}), (1\text{Hz}\sim10\text{kHz})$ $\pm(1.0\%+20\text{digits}), (10\text{Hz}\sim20\text{kHz})$ $\pm(3.0\%+30\text{digits}), (20\text{Hz}\sim50\text{kHz})$
	2V	100 μ A	$\pm(0.5\%+10\text{digits}), (45\text{Hz}\sim300\text{Hz})$ $\pm(0.8\%+40\text{digits}), (300\text{Hz}\sim10\text{kHz})$ $\pm(1.0\%+20\text{digits}), (10\text{Hz}\sim20\text{kHz})$ $\pm(3.0\%+30\text{digits}), (20\text{Hz}\sim50\text{kHz})$
	20V	1mV	$\pm(0.5\%+10\text{digits}), (45\text{Hz}\sim300\text{Hz})$ $\pm(0.8\%+40\text{digits}), (300\text{Hz}\sim10\text{kHz})$ $\pm(1.0\%+20\text{digits}), (10\text{Hz}\sim20\text{kHz})$ $\pm(3.0\%+30\text{digits}), (20\text{Hz}\sim50\text{kHz})$
	200V	10mV	$\pm(0.5\%+30\text{digits}), (20\text{Hz}\sim50\text{kHz})$
	750V	100mV	$\pm(0.5\%+10\text{digits}), (45\text{Hz}\sim1\text{kHz})$
DC CURRENT	2mA	0.1 μ A	$\pm(0.5\%+1\text{digit})$
	20mA	1 μ A	
	200mA	10 μ A	
	2A	100 μ A	$\pm(0.75\%+3\text{digit})$
	10A	10 μ A	
AC CURRENT	2mA	0.1 μ A	$\pm(1.0\%+10\text{digits}), (45\text{Hz}\sim10\text{kHz})$
	20mA	1 μ A	
	200mA	10 μ A	$\pm(2.0\%+20\text{digits}), (10\text{Hz}\sim20\text{kHz})$
	2A	100 μ A	$\pm(1.0\%+10\text{digits}), (45\text{Hz}\sim2\text{kHz})$
	10A	10mA	
RESISTANCE	200 Ω	10M Ω	$\pm(2.0\%+5\text{digits})$
	2k Ω	0.1 Ω	$\pm(0.2\%+2\text{digits})$
	20k Ω	1 Ω	
	200k Ω	10 Ω	
	2M Ω	100 Ω	$\pm(0.5\%+2\text{digits})$
	20M Ω	1k Ω	
FREQUENCY	20KHz	1Hz	$\pm(1.0\%+3\text{digits})$
	200KHz	10Hz	$\pm(2.0\%+3\text{digits})$
TR hfe	BASE CURRENT : 3.5 μ A, Vce : Approx. 4.5V		
DIODE CONTINUITY	TEST VOLTAGE : 4.5V Approx., Maximum test Current : 1mA Threshold : 200 Ω or Less		